


K-STYLE GUTTER WITH ROOF FLANGE

* NOTES

- .050" provided with splice plates
- 24 ga., 22 ga., .032", .040" all need field notched lap joints
- Stainless steel pop rivets provided
- Unless otherwise noted, fabrication of miters and accessories are furnished standard utilizing a non-penetrating quicklock joint, then factory sealed watertight
- Welded accessories require minimum material thickness of .050"
- For non-90 miters, see separate print approval
- Product should be installed per provided installation instructions



DIMENSIONS

Fill out additional information on the drawing above.

GUTTER SIZE	A	B	C	D
<input type="checkbox"/> 6"	4 1/2"	6"	5"	3 7/8"
<input type="checkbox"/> 7"	5 3/8"	7"	5 7/8"	4 5/8"
<input type="checkbox"/> 8"	6"	8"	6 1/8"	5 3/8"

MATERIAL

- 24 Ga. Galv. Steel
 22 Ga. Galv. Steel
 .040" Aluminum
 .050" Aluminum
 .063" Aluminum
 OTHER: _____
- Color: _____
Finish: _____
- Substrate:
If substrate is not given, wood fasteners will be provided.
- Wood
 Masonry
 Metal

QUANTITIES

- _____ Lineal Feet (10'-0" Lengths)
 _____ Outside Miter (90°)
 _____ Inside Miter (90°)
 _____ Right Endcaps
 _____ Left Endcaps
 _____ Expansion Joints

Accessory Type* : Quicklock (Default) Welded (Surcharge)
(WELDED OPTION FOR MITERS ONLY)

NOTE: ONE EXPANSION JOINT INCLUDES: (2) ENDCAPS, (1) OUTSIDE COVER PLATE AND (1) TOP PLATE

PROJECT INFO

Project Name: _____

Architect: _____

Roofing Contractor: _____

Project Type:

By selecting this box you have verified and confirmed that dimensions, sizes, and quantities are correct. All products will be installed in strict accordance with printed instructions.

Date: _____

Hickman Edge Systems

4 Commerce Way
 Arden, NC 28704
 Phone: 828-676-1700
 www.hickmanedgesystems.com

SHT# 1 of 1

DATE: 10/25/21

DRN BY: JJC

CKD BY: MM

DWG #: 64012-37329

REV: A